

FV 15 Specifications

Model:	2-channel track					
	draw rod ¹	01-4643 with clip		01-4644 with tension lever		
	3-channel track					
	draw rod ¹ /pull cord ²	01-4651 with clip		01-4652 with tension lever		
	4-channel track					
	draw rod ¹ /pull cord ²	01-4659 with clip		01-4660 with tension lever		
5-channel track	draw rod ¹ /pull cord ²	01-4667 with clip		01-4672 with tension lever		
	Electric drive 230 V	01-4671 with clip		01-4672 with tension lever		
	6-channel track					
draw rod ¹ /pull cord ²	01-4675 with clip		01-4676 with tension lever			
	Electric drive 230 V	01-4679 with clip		01-4680 with tension lever		
Fitted sizes:	Operation / Function	Blind unit sizes		Panel sizes		
		Min. width	Max. width*	Min. width	Max. width	Max. height
	Freely movable	from 30 cm	up to 590 cm	30 cm	160 cm	350 cm
		* Track length without joint up to max. 590 cm				
Description:	MHZ panel blinds made of combinable aluminium profiles, with panel carrier. Operation options: Freely movable elements, draw rod, pull cord or electric drive. Mounting systems for wall and ceiling.					
Profiles:	Torsion-proof profiles made of extruded aluminium. Profile height 15 mm, silver anodised, matt E6/EV1 (112) or white powder-coated RAL 9016 (171), 2-, 3-, 4- and 5-channel profiles, plus a 3-channel profile with web for combinations. Hidden mounting system with clip or tension lever. Joint connectors for lengths exceeding 590 cm.					
Panel carrier:	Plastic panel carrier with rolls or gliders, white or silver, up to 160 cm length, compl. with hook tape and accessories (draw rod eyelet, catch, limit stop), incl. internal weight profile made of extruded aluminium, height 25 mm, width 6.2 mm, matt silver anodised E6/EV1 (112) or white powder-coated RAL 9016 (171). External weight profile made of extruded aluminium, height 25 mm, width 8 mm, matt silver anodised E6/EV1 (112) or white powder-coated RAL 9016 (171).					
Fabric panels:	Panels made of textile fabric, textile fleece or foil. See MHZ collection for fabric colour (colour no.) Information regarding special properties: See collection regarding suitability for PC workstations, flame retardant properties etc. Fabric panel incl. loop tape, optionally with hemstitch, cord piping, lead weighted tape or without hem.					
Mounting accessories:	Easy, fast and hidden ceiling installation, optionally with clips or tension levers. Wall installation with various brackets (only in combination with clips).					
Operation freely movable:	Track with end caps, loose panel carriers for any configuration. Optional: draw rods in various versions.					
Draw rod operation:	Track with end caps, panel carriers in various configurations. draw rods in various versions.					
Pull cord operation:	Track with cord operation, panel carriers in various configurations. Optimised operation and complete opening and closing of panels (up to outer edge of track) thanks to front-side cord exit. Various versions with 3, 4, 5, 6 or more channels. Safety tensioner for child safety included.					
Electric powered operation:	Track with electric drive, panel carriers in various arrangements. Electric drive 230 V/50 Hz, speed approx. 20 cm/sec, incl. thermal circuit breaker, factory-adjusted mechanical limit switches. Various versions with 5, 6 or more channels. For electric control units see www.mhz.de .					

FV 15
track

¹ Draw rod not included.

² Pull cord at a surcharge.

FV 15 Profiles and dimensions

Scale 1:1

Scale 1:2

