◆ MHZ

CARAT_24 Specifications

Model:	2-channel track	**01-4222** with clip
	3-channel track	**01-4223** with clip
	4-channel track	**01-4224** with clip
	5-channel track	**01-4225** with clip

Fitted sizes:

Operation / Function	Blind unit sizes		Panel sizes		
	Min. width	Max. width*	Min. width	Max. width	Max. height
Freely movable	from 40 cm	up to 590 cm	40 cm	160 cm	350 cm

* Track length without joint up to max. 590 cm

Description:
MHZ panel blinds made up of aluminium profiles, with end caps and panel carriers.
Freely movable elements.
Hook-and-loop-tape-free simple threading in of the hanging into the panel carrier by piping cord system
Simple attachment and removal of the panel carrier into the rail runs right from below.
Mounting systems for wall and ceiling
(clip fixing).

Profiles:
Torsion-proof profiles made of extruded aluminium. Profile height 23 mm, 2-, 3-, 4- and 5-channel profiles.
Hidden fixing system with clip. Joint connectors for lengths exceeding 590 cm.

Hardware colours:
silver anodized, matt E6/EV1 (112), white powder-coated RAL 9016 (171) or
stainless steel look, brushed (253)

Panel carrier:
panel carrier made of extruded aluminium, silver anodised, matt E6/EV1, with rolls made of plastic. End caps
with clamping lever, silver, up to 160 cm, incl. internal weight profile made of extruded aluminium. Height 25
mm, width 6.2 mm, matt silver anodised, matt E6/EV1 (112),
white powder-coated RAL 9016 (171), External weight profile made of extruded aluminium, height 25 mm,
width 8 mm, matt silver anodised E6/EV1 (112), white powder-coated RAL 9016 (171) or brushed stainless
steel look (253).

Fabric panels:
Panels made of textile fabric, textile fleece or foil. See MHZ collection for fabric colour (colour no.)

Information regarding special properties:
See collection regarding suitability for PC workstations, flame retardant properties etc.
Fabric panel incl. piping for panel carrier, with hemstitch or with cord piping for the weight profile.

Mounting accessories:
Simple and quick, concealed ceiling mounting using clips.

Operation freely movable:
Track with end caps, loose panel carriers for any configuration.

Subject to technical changes I *Edition 05.2014*
Recommended non-binding list prices in euros (incl. VAT)

21

◆ MHZ

CARAT_24 Profiles and dimensions

Scale 1:1

Scale 1:1

13 mm

24 mm

16 mm

16 mm

height of panel up to lower edge of weighted bar
(ordering height)

height of panel up to lower edge of hemstitch

8

6,2

5,3

25

25

11

3,2

gap aprox. 1-3 cm

33,2 mm

23,2 mm

49,2 mm

65,2 mm

81,2 mm